



Door Frame or Perimeter Seals

RP78 Si (REPLACES RP78)

M



An acoustic medium temperature smoke door frame seal designed for installation on door stops, its aluminium carrier is sturdy and slotted for adjustment with concealed fixings. It is quick and easy to install around the jamb and head and can be fitted without removing the door.

RP78 Si can be mitred or butt jointed.

Location Head and jambs on single or double butt hinged doors.

Min/Max Gap 0mm - 6mm.

Seal Sizes

Available in stock lengths or door set sizes.

Standard Finish

Aluminium anodised 15 microns. Satin Clear (Silver) or Bronze finish.

P.E. Paint (extra cost). Is a two pack polyester enamel colour match finish which is equal to or exceeds powdercoat finish.

Fixing Method

Zinc plated, cross recess head S.T. screws and self-drilling screws of the appropriate size are supplied.

Seal Material

Silicon Rubber (SE) (grey).

Replacement Seal RP394 Si.

Used in conjunction

RP8 Si, RP16 Si, RP38 Si, RP99 Si, RP70 Si.

Approvals

Acoustic AUZ/NZ: Conforms to BCA Sec. F5. 5. Tested to AS 1191, AS 1045, AS/NZS 1276.

UK/EU: Conforms to Approved Document E. Tested to BS EN ISO140.3 (similar to BS EN ISO 717.1, BS 2750, BS 5821).

Fire & Smoke AUS/NZ:

Conforms to BCA Spec. C3.4 Tested to AS 1530.4, AS/NZS1905.1 & AS.NZS 1530.7.

UK/EU: Conforms to Approved Document B. Tested to ISO CD 5925-1 (similar to BS EN 1634.1, BS 476 Part 20 & 22,Sec.31.1).

